

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/047639 A1

(51) International Patent Classification⁷: **A61B 5/055**, 6/04

(21) International Application Number:
PCT/IB2003/005305

(22) International Filing Date:
19 November 2003 (19.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/429,703 27 November 2002 (27.11.2002) US

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **EVERETT, Dennis, K.** [US/US]; 595 Miner Road, Cleveland, OH 44143 (US).
BIELAWSKI, Timothy [US/US]; 595 Miner Road, Cleveland, OH 44143 (US).
CUMPSON, Patrick, T. [US/US]; 595 Miner Road, Cleveland, OH 44143 (US).

(74) Common Representative: **KONINKLIJKE PHILIPS ELECTRONICS N.V.**; c/o Lundin, Thomas, M., 595 Miner Road, Cleveland, OH 44143 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR AUTOMATIC SELF-ALIGNING DOCKING OF A COUCH WITH A MAGNETIC RESONANCE IMAGING SCANNER



(57) Abstract: A docking assembly connected to a movable couch (30) docks the couch with an imaging apparatus (10). Couch alignment surfaces (72) mate with corresponding alignment surfaces (64) of a connecting region (50) of the imaging apparatus (10) to define a docked position of the movable couch (30) with respect to the imaging apparatus. A docking sensor (160) detects the movable couch (30) approaching the docked position. A latch (82) mates with the connecting region (50) of the imagingto apparatus (10). An actuator (130, 154) cooperates with the latch (82) to bias the movable couch (30) into the docked position responsive to a signal produced by the docking sensor (160).



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**METHOD AND APPARATUS FOR AUTOMATIC SELF-ALIGNING DOCKING OF A
COUCH WITH A MAGNETIC RESONANCE IMAGING SCANNER**

The following relates to the diagnostic imaging arts. It particularly relates to the docking and undocking of a couch or other movable subject support with a magnetic resonance imaging apparatus. The following relates more generally to
5 rapid, safe, precise, and convenient transfer of a patient or other imaging subject into and out of various types of diagnostic imaging scanners such as magnetic resonance imaging scanners, computed tomography imaging scanners, nuclear cameras, positron emission tomography scanners, and the like.

10 In medical diagnostic imaging, an issue arises in the transfer of an imaging subject to and from the imaging apparatus. In many cases, the subject is disabled and unable to assist in the transfer process. In some instances it is important to preserve patient position.

15 Typically, the patient is placed on a wheeled patient couch or other movable subject support that is adapted to mechanically dock with the medical diagnostic magnetic resonance imaging scanner or other imaging apparatus. In one known approach, a locking mechanism that locks the couch to the
20 imaging apparatus is triggered by operation of a brake pedal of the patient couch. Once connected, a conveyor belt of the imaging apparatus is linked with a patient supporting pallet or top of the patient couch, and the patient and pallet are transported into a magnet bore of the magnetic resonance
25 imaging apparatus for imaging.

After the imaging session is complete, the patient and pallet are transported back and reconnected to the patient couch base. The operator disconnects the conveyor belt of the

imaging apparatus from the patient couch. The brake pedal is released, which also unlocks the patient couch from the subject support, and the patient couch is wheeled away.

These patient transfer systems rely upon substantial
5 operator input and coordination to dock and undock the patient successfully. The couch is manually aligned and moved into the docking position, and the locking mechanism of the couch with the imaging apparatus relies upon accuracy of such manual alignment. Moreover, there is a substantial possibility of
10 operator error causing patient injury and/or damage to the couch and/or imaging apparatus if, for example, the couch is undocked prior to disconnection of the conveyor belt linkage.

The present invention contemplates an improved apparatus and method that overcomes the aforementioned
15 limitations and others.

According to one aspect, a docking assembly is disclosed. The docking assembly is connected to a movable
20 subject couch for docking the movable subject couch with an imaging apparatus. Couch alignment surfaces mate with corresponding imaging apparatus alignment surfaces of a connecting region of the imaging apparatus to define a docked position of the movable subject couch with respect to the
25 imaging apparatus. A docking sensor detects the movable subject couch approaching the docked position. A latch mates with the connecting region of the imaging apparatus. An actuator cooperates with the latch to bias the movable subject couch into the docked position in response to the docking sensor
30 detecting that the couch has approached the docking position.

According to another aspect, a method is provided for docking a movable subject support couch with an imaging apparatus. The movable subject support couch is moved toward

the imaging apparatus. Responsive to the moving, a latch connected with the movable subject support couch mates with a connecting region of the imaging apparatus. The movable couch approaching a docked position with respect to the imaging apparatus is detected. Responsive to the detecting, the movable subject support couch is biased into the docked position using the mated latch as a first force anchor.

One advantage resides in reduced operator actions involved in subject docking and undocking.

Another advantage resides in a reduced likelihood of damage to the patient support and/or the imaging apparatus due to operator error in the docking or undocking.

Yet another advantage resides in improved docking and undocking reliability.

Still yet another advantage resides in self-alignment of the couch or other movable subject support with the imaging apparatus.

Numerous additional advantages and benefits will become apparent to those of ordinary skill in the art upon reading the following detailed description of the preferred embodiments.

The invention may take form in various components and arrangements of components, and in various process operations and arrangements of process operations. The drawings are only for the purpose of illustrating preferred embodiments and are not to be construed as limiting the invention.

FIGURE 1 shows a side view of a magnetic resonance imaging apparatus with a movable couch docked therewith.

FIGURE 2 shows a partial sectional view of the magnetic resonance imaging apparatus and docked movable couch of FIGURE 1.

FIGURE 3 shows a connecting region of the magnetic resonance imaging apparatus of FIGURES 1 and 2 that cooperates with a docking assembly of the movable couch in docking the movable couch with the magnetic resonance imaging apparatus.

5 FIGURE 4 shows an overhead perspective view of a lower portion of the movable couch including components of the docking assembly.

FIGURE 5 shows a perspective view from below of the lower portion of the movable couch shown in FIGURE 4.

10 FIGURE 6 shows a perspective view of a portion of the docking assembly including an actuator, connecting rods, mechanical fittings, a spring cartridge assembly, a divider plate, and latches.

15 FIGURE 7 shows a perspective view of one of the latches including a guide plate.

FIGURE 8 shows a perspective view of the latch of FIGURE 7 with the guide plate removed.

20 FIGURE 9 diagrammatically shows a state diagram of a state machine controller that controls the docking and undocking processes.

With reference to FIGURES 1 and 2, a magnetic resonance imaging apparatus 10 includes a housing 12 that encloses at least a main magnet which is preferably superconducting and cryoshrouded. The housing 12 defines a bore 14 inside which a subject is placed for imaging. Magnetic field gradient coils for spatially encoding the magnetic resonance signals are enclosed in the housing 12 or are arranged in the bore 14, as are one or more radio frequency coils and other optional components that are cooperatively used to generate, tailor, and detect magnetic resonance signals of the imaging subject.

A motorized belt or chain drive 20 passes through the bore 14. The belt 20 is linearly movable to position or move an imaging subject axially within the bore 14. The motorized belt 20 includes a portion 22 extending beyond a first side 24 of the housing 12 to enable the subject to be positioned with a portion extending outside the bore 14 on the first side 24.

On a second side 26 of the housing 12, the belt 20 cooperates with a movable subject support pallet or couch top 28 of a couch assembly 30 to define a continuous motorized subject transport that extends on both sides 24, 26 of the housing 12. Specifically, a coupling element 32 couples the belt 20 of the magnetic resonance imaging apparatus 10 with a subject support belt portion 34.

The movable couch 30 is detachably attached to the imaging apparatus 10. To enable the couch 30 to be moved when it is detached from the imaging scanner 10, the couch 30 includes wheels 40, rolling castors, or the like. One or more wheel brakes 42 are selectively operated to immobilize the couch 30. Preferably, the couch 30 also includes a height adjustment mechanism 44 for vertically aligning the coupling element 32 with the belt 20 of the imaging apparatus 10.

With continuing reference to FIGURES 1 and 2, and with further reference to FIGURE 3, the magnetic resonance imaging apparatus 10 includes a connecting region 50 that provides alignment and force anchoring for aligning and securing the movable couch 30 with the imaging apparatus 10. In the illustrated embodiment, the connecting region 50 includes two latching blocks 52 on opposite sides of an electronic connector 54. The electrical connector 54 provides for optional electrical communication between the imaging apparatus 10 and the movable couch 30, for example to communicate sensor readings therebetween or to deliver electrical power and/or control signals from the imaging apparatus 10 to the movable

couch 30. Each latching block 52 includes a camming surface 56 for camming a latch or other mating component of the subject support 30 onto the latching block 52.

5 Placement of the two latching blocks 52 on opposite sides of the electrical connector 54 advantageously arranges the force anchoring symmetrically with respect to the imaging apparatus 10. However, if the optional electrical connector 54 is omitted, a single centrally positioned latching block can be employed. Of course, more than two latching blocks can also be
10 included to provide additional force anchoring points.

 The connecting region 50 also includes a tongue 60 that extends away from the imaging apparatus 10. The tongue 60 includes camming surfaces 62 for facilitating lateral alignment of the couch 30 with the imaging apparatus 10 during docking.
15 The tongue 60 further includes alignment surfaces 64 disposed on the tongue edges that cooperate with corresponding surfaces of the docking assembly to define a docked position with the movable couch 30 in line with the bore 14. A mounting plate 66 secures the connecting region 50 with the second side 26 of the
20 imaging apparatus 10. Alternatively, the connecting region 50 can be integrated with the housing 12. Preferably, the connecting region 50 includes stops 68 that limit movement of the couch 30 toward the imaging apparatus 10 and limit skewing to assure that the couch 30 is in line with the bore 14.

25 With continuing reference to FIGURES 1-3 and with further reference to FIGURES 4-8, a lower portion 70 of the movable couch 30 includes a docking assembly that cooperates with the connecting region 50 of the magnetic resonance imaging apparatus 10 to detachably secure the movable couch 30 with the
30 magnetic resonance imaging apparatus 10. The docking assembly includes alignment surfaces 72 with rollers or bearings 74 that cooperate with the alignment surfaces 64 of the tongue 60 of the connecting region 50 of the imaging apparatus 10 to define

the docked position of the movable couch 30 relative to the imaging apparatus 10. The rollers or bearings preferably also serve as camming surfaces that cooperate with the camming surfaces 62 of the tongue 60 of the connecting region 50 to
5 urge the movable couch 30 laterally toward the docked position as the couch 30 approaches the imaging apparatus 10.

The docking assembly further includes latches 82 disposed at a forward end 84 of the couch 30 that detachably latch with the two latching blocks 52. In the illustrated
10 embodiment, there are two latches 82 corresponding to the two latch blocks 52. An alternative embodiment with a single centrally located latch block will typically include a single corresponding latch, rather than the two latches shown.

In the illustrated embodiment, each latch 82 includes
15 a hook 86 that is spring-biased to a closed position by a leaf spring 88. (Best seen in FIGURES 7 and 8). The leaf spring 88 is secured to a guide block 90 at one end, and is preferably secured to the hook 86 by a fastener 92. The guide block is secured to the lower portion 70 of the movable couch 30. (Best
20 seen in FIGURE 5). The hook 86 of each latch 82 pivots about a clevis pin 94 that in turn is connected with a clevis yoke 96 to allow the hook 86 to open in opposition to the biasing force produced by the leaf spring 88.

The clevis yoke 96 is fastened to a guide rod 100
25 that slidably passes through the guide block 90. A guide plate 102 is secured to the guide block 90 via fasteners 104. (Note that the guide plate 102 is shown in FIGURE 7, and is removed in FIGURE 8 to show underlying components). The guide plate 102 includes a first narrow slot 106 that cams the clevis pin 94,
30 and a second wider slot 108 that cooperates with a camming pin 110 to guide opening and closing of the latch 82.

The guide rod 100 of each of the two latches 82 connects with a divider plate 114 that distributes an actuator

force between the two latches 82. As shown in FIGURE 6, ends of the guide rods 100 can connect to the divider plate 114. Alternatively, as shown in FIGURE 5, each guide rod 100 can connect at an intermediate point such that the guide rod 100
5 also passes through a caster weldment of the couch 30 to assist in guiding and dividing actuator force between the two guide rods 100.

The divider plate 114 in turn connects with a front connecting rod 120 via a pivotable clevis block 122 that is
10 pinned to the divider plate 114. The front connecting rod 120 includes a threaded opposite end that threads into a spring cartridge assembly 130. A rear connecting rod 134 has a threaded end that threads into the spring cartridge assembly 130 and extends away from the forward end 84 of the movable
15 couch 30 through a guide block 136 toward a rear end 138 of the couch 30. The rear connecting rod 134 connects with another clevis block 142 that is pinned to a pivotable drive link 146. The pivotable drive link pivots about a pivot 150 fixed to the weldment of the movable couch 30.

20 An actuator motor 154 delivers the actuator force to the pivotable drive link 146 at an end of the drive link 146 opposite the pivot 150. A second class lever is thus defined in which the load-coupling clevis block 142 is arranged between the applied force produced by the actuator motor 154 and a
25 lever fulcrum defined by the pivot 150. The hooks 86 are cammed apart during movement of the couch 30 and are biased by the leaf springs 88 onto the blocks 52. To undock, the actuator motor 154 applies a force to the linkage which moves the hooks 86 apart, away from the blocks 52. In one suitable embodiment,
30 the actuator motor 154 is a battery-driven 24 volt self-locking linear actuator motor.

With continuing reference to FIGURES 1-8, the docking assembly further includes various sensors for sensing various

stages of docking and undocking. In the illustrated embodiment, these sensors include a start dock sensor **160** suitably embodied as a plunger switch that is activated or turned on (that is, plunger depressed) when the movable couch **30** approaches the docked position such that the plunger contacts a surface of the connecting region **50** of the imaging apparatus **10**. A flipper switch **162** similarly detects when the movable couch **30** is secured in the docked position, and when the couch **30** is substantially free from the docked position during undocking. A brake switch detects whether the wheel brake **42** is on or off.

Optical switch sensors **164** indicate a state of the drive link **146**. In a preferred embodiment, three drive link optical switch sensors **164** indicate whether the drive link **146** is in: (i) an undocked position in which the drive link **146** is pivoted toward the rear end **138** of the couch **30**; (ii) a docked position in which the drive link **146** is pivoted toward the front end **84** of the couch **30**; or (iii) a ready-to-dock position in which the drive link **146** is pivoted into an intermediate position between the front end **84** and the rear end **138** of the couch **30**.

With continuing reference to FIGURES 1-8 and with further reference to FIGURE 9, the docking assembly preferably includes a state machine controller whose state diagram **200** is schematically represented in FIGURE 9. The state machine controller is preferably embodied by a microprocessor or microcontroller disposed on the movable couch **30** that monitors the sensors and implements the state diagram **200**.

The exemplary state diagram **200** includes four states. In a ready-to-dock state **202**, the optical sensor **164** indicates the ready-to-dock position of the drive link **146**, and the start dock plunger sensor **160**, the flipper switch **162**, and the brake switch are off. In a docked state **204**, the optical sensor **164** indicates the docked position of the drive link **146**, the start

dock plunger sensor **160** and the flipper switch **162** are both activated, but the brake switch is off. A docked-and-braked state **206** is similar to the docked state **204** except that the brake sensor indicates the brake is on. In an undocked state
5 **208**, the optical sensor **164** indicates the undocked position of the drive link **146**, the flipper switch **162** is activated, and the brake switch is off.

The exemplary state diagram **200** suitably implements a docking process that starts at the ready-to-dock state **202**. An
10 operator rolls the movable couch **30** on its wheels **40** toward the connecting region **50** of the imaging apparatus **10**. During this movement, the camming surfaces **62** of the connecting region **50** of the imaging apparatus **10** contact and cam with the rollers **74** or other camming surfaces of the docking assembly to urge the
15 couch **30** toward the docked position. Similarly, the hooks **86** of the latches **82** contact the camming surfaces **56** of the latch blocks **52** of the connecting region **50** and cam open against the biasing force exerted by the leaf springs **88**. As continued movement of the couch **30** moves the hooks **86** past the camming
20 surfaces **56**, the hooks **86** close onto the latching blocks **52** due to the biasing of the leaf springs **88**.

Continued movement of the couch **30** toward the docked position causes the start dock plunger **160** to be pushed in, triggering a transition from the ready-to-dock state **202** to the
25 docked state **204**. The actuator motor **154** is driven to pivot the drive link **146** from the ready-to-dock position to the docked position. This movement produces an actuator force F_1 pulling on the rear connecting rod **134**. Initially, the actuator force F_1 transfers through the rear connecting rod **134**, the spring
30 cartridge assembly **130**, and the front connecting rod **120**, and is distributed by the divider plate **114** and the guide rods **100** to the two latches **82**. Thus, the actuator force F_1 is a tensile force acting between a rear force anchor point corresponding to

the motor 154 and the drive link 146, and a front force anchor point defined by the connection of the latches 82 onto the latch blocks 52.

The tensile actuator force F_1 draws the movable couch
5 30 into the docked position. Once docked, the motor 154 continues to operate to transfer and store a predetermined amount of mechanical energy in the spring cartridge assembly 130. In a preferred embodiment, the spring cartridge assembly 130 is loaded to about 55 kg. Once the spring cartridge
10 assembly 130 is loaded to the desired value, the motor 154 ceases operation.

Thus, when the motor 154 ceases operation the movable couch 30 remains biased and secured in the docked position by the loaded spring cartridge assembly 130. The docked state 204
15 is indicated by the optical sensors 164. To ensure the movable couch 30 is secured, the user is preferably prompted by a display or other indicator to engage the brakes. The operator engages the wheel brake 42. Engaging the wheel brake 42 activates the brake switch and places the docking assembly into
20 the docked-and-braked state 206.

Once docked and braked, the operator connects and locks the belt coupling element 32 to the belt 20 of the imaging apparatus 10. Once the connection is sensed, a lock which locks the subject pallet or couch top 28 to the couch 30
25 is released. The belt 20 transfers the subject pallet 28 into the magnet bore 14 of the imaging apparatus 10. The operator causes the imaging apparatus 10 to perform selected magnetic resonance imaging operations on the subject, and transfers the subject back to the movable couch 30 via the linked belts 20,
30 34.

Once the pallet 28 is locked to the couch 30, the operator can initiate undocking by decoupling the coupling element 32 and releasing the wheel brake 42. Preferably,

transition from the docked-and-braked state **206** to the undocked state **208** is initiated by release of the wheel brake **42**. However, the transition preferably also is contingent upon a tabletop sensor **212** (operatively represented in FIGURE 9) indicating that the conveyor belt coupling element **32** is unlocked and the pallet **28** is locked to the couch **30**. This reduces the likelihood of damage to the conveyor belts **20**, **34** or the coupling element **32**.

To undock, the motor **154** operates in a reverse direction to pivot the drive link **146** from the rearward docked position to the forward undocked position. This exerts an actuator force F_2 on the rear connecting rod **134** directed toward the front end **84**. Initially, the actuator force F_2 transfers through the rear connecting rod **134** to the spring cartridge assembly **130** to unload the spring cartridge assembly **130**. That is, in the exemplary embodiment the 55 kg stored in the spring cartridge assembly **130** is unloaded.

Once the spring cartridge assembly **130** is unloaded, the actuator force F_2 transfers through the rear connecting rod **134**, the spring cartridge assembly **130**, and the front connecting rod **120**, and is distributed by the divider plate **114** and the guide rods **100** to the two latches **82**. The actuator force F_2 drives each hook **86** forward. During this forward motion, the clevis pin **94** cams in the first narrow slot **106** and the camming pin **110** cams in the second wider slot **108** of the guide block **90** to guide the hook **86** into an open position against the biasing force of the leaf spring **88**.

When the drive link **146** reaches the undocked position as indicated by the drive link optical switch sensors **164**, the latches **82** are retained in the open position. The operator can then move the couch **30** away from the imaging apparatus **10**. The movement draws the opened latches **82** past the latch blocks **52** of the connection region **50** of the imaging apparatus **10**.

Continued movement causes the flipper switch **162** to deactivate, indicating that the latches **82** are clear of the latching blocks **52**.

Deactivation of the flipper switch **162** initiates a
5 transition from the undocked state **208** to the ready-to-dock
state **202**. To make this transition, the motor **154** moves the
drive link **146** from the undocked position to the intermediate
ready-to-dock position. The movement transfers through the rear
connecting rod **134**, the spring cartridge assembly **130**, and the
10 front connecting rod **120**, and is distributed by the divider
plate **114** and the guide rods **100** to the two latches **82**. The
actuator force F_2 holding the hooks **86** open is released so that
the closing bias provided by the leaf springs **88** causes the
hooks **86** to be biased into the closed position.

15 Docking and undocking of the movable couch **30** with
the exemplary magnetic resonance imaging apparatus **10** is
described herein. However, those skilled in the art can readily
adapt the described docking assembly to perform docking and
undocking of a patient couch or other movable imaging subject
20 support with other types of magnetic resonance imaging
scanners, or with a computed tomography imaging apparatus, a
nuclear camera, a positron emission tomography imaging
apparatus, a radiotherapy apparatus, or the like.

Having thus described the preferred embodiments, the invention is now claimed to be:

1. A docking assembly connected to a movable subject couch (30) for docking a movable subject couch (30) with an imaging apparatus (10), the docking assembly including:

couch alignment surfaces (72) that mate with corresponding imaging apparatus alignment surfaces (64) of a connecting region (50) of the imaging apparatus (10) to define a docked position of the movable subject couch (30) with respect to the imaging apparatus (10);

a docking sensor (160) that detects the movable subject couch (30) approaching the docked position;

a latch (82) that mates with the connecting region (50) of the imaging apparatus (10); and

an actuator (130, 154) that cooperates with the latch (82) to bias the movable subject couch (30) into the docked position in response to the docking sensor (160) detecting that the couch (30) has approached the docking position.

2. The docking assembly as set forth in claim 1, further including:

rolling elements (74) arranged between the couch alignment surfaces (72) and the corresponding imaging apparatus alignment surfaces (64) of the connecting region (50) of the imaging apparatus (10).

3. The docking assembly as set forth in claim 1, wherein the docking assembly further includes:

couch camming surfaces (62) that cooperate with camming surfaces (74) of the connecting region (50) of the imaging apparatus (10) to cam the movable subject couch (30) laterally

toward alignment with the docked position as the movable subject couch (30) approaches the imaging apparatus (10).

4. The docking assembly as set forth in claim 1, wherein the latch (82) includes:

a biasing spring (88); and

a hook (86) that is biased by the biasing spring (88) toward a closed position, the hook (86) being cammed opened in opposition to the biasing spring (88) by a camming surface (56) of a latch block (52) as the movable subject couch (30) approaches the docked position, the biasing spring (88) biasing the hook (86) to close onto the latch block (52) as the hook (86) moves past the camming surface (56) and ceases contact therewith.

5. The docking assembly as set forth in claim 1, wherein the actuator (130, 154) includes:

an electric motor (154); and

a mechanical energy storage element (130) interposed between the motor (154) and the latch (82), the mechanical energy storage element (130) cooperating with the latch (82) to bias the movable subject couch into the docked position when the motor (154) is not delivering mechanical energy.

6. The docking assembly as set forth in claim 5, wherein the mechanical energy storage element (130) includes a spring (130) interposed between the motor (154) and the latch (82).

7. The docking assembly as set forth in claim 6, wherein the actuator (130, 154) further includes:

a drive shaft (120, 134, 146) arranged between the motor (154) and the latch (82), the motor (154) driving the drive shaft (120, 134, 146) in a first direction to secure the latch

(82) onto the latch block (52) of the connecting region (50) of the imaging apparatus (10), the spring (130) storing energy received from the motor (154) during the driving in the first direction, the stored energy continuing to bias the latch (82) on the latch block (52) after the driving in the first direction ceases.

8. The docking assembly as set forth in claim 7, further including:

an undock camming surface (108, 110) that communicates with the latch (82) to cam the latch (82) open when the motor (154) drives the drive shaft (120, 134, 146) in a second direction opposite the first direction.

9. The docking assembly as set forth in claim 1, further including:

an electronic controller (200) communicating with the actuator (130, 154) and the docking sensor (160), the electronic controller (200) operating the actuator (130, 154) to cooperate with the latch (82) to bias the movable subject couch (30) into the docked position in response to the docking sensor (160) detecting the movable subject couch (30) approaching the docked position.

10. The docking assembly as set forth in claim 9, wherein the electronic controller (200) monitors a state of the docking assembly, the docking assembly being in one of a plurality of states including:

a ready-to-dock state (202) in which the latch (82) is biased into a closed position and the electronic controller (200) is waiting for the docking sensor to detect the movable subject couch (30) approaching the docked position;

a docked state (204, 206) in which the latch (82) is biased into the closed position and secured to the connecting region (50) by the actuator (130, 154); and

an undocking state (208) in which the latch is biased into an open position by the actuator.

11. The docking assembly as set forth in claim 10, further including:

a tabletop lock sensor (212) that indicates a locked condition of a subject transfer pallet (28) of the movable subject couch (30), the electronic controller (200) monitoring the tabletop lock sensor (212) and prohibiting a docking assembly state transfer from the docked state (204, 206) to the undocking state (208) when the tabletop lock sensor (212) indicates an unlocked condition.

12. The docking assembly as set forth in claim 10, further including:

an actuator sensor (164) that indicates a position of the actuator (130, 154), the electronic controller (200) identifying the docking assembly state based on at least the docking sensor (160) and the actuator sensor (164).

13. A magnetic resonance imaging apparatus including:

a housing (12) that houses at least a main magnet and magnetic field gradient coils and defines a bore (14); and

the connecting region (50) of the docking assembly as set forth in claim 1 secured to the housing (12).

14. The magnetic resonance imaging apparatus as set forth in claim 13, wherein the connecting region (50) further includes:

a tongue (60) extending from the housing (12), the tongue (60) defining the imaging apparatus alignment surfaces (64); and

a latch block (52) disposed on the tongue, the latch (82) selectively latching onto the latch block (52).

14. A couch including:

a wheeled subject support (30); and

a docking assembly set forth in claim 1 for docking the wheeled subject support with a diagnostic imaging apparatus.

15. The couch as set forth in claim 14, wherein the actuator (130, 154) includes:

a motor (154) disposed on the movable subject support (30) that selectively drives the latch (82) to mate with the connecting region (50) of the imaging apparatus (10).

16. The couch as set forth in claim 15, wherein the actuator (130, 154) further includes:

a spring (130) disposed between the motor (154) and the latch (82), the spring (130) being mechanically loaded when the motor (154) drives the latch (82) to mate with the connecting region (50), the loaded spring biasing the latch (82) into the mated position when the motor (154) ceases the driving.

17. A method for docking a movable subject support couch (30) with an imaging apparatus (10), the method including:

moving the movable subject support couch (30) toward the imaging apparatus (10);

responsive to the moving, mating a latch (82) connected with the movable subject support couch (30) with a connecting region (50) of the imaging apparatus (10);

detecting the movable couch (30) approaching a docked position with respect to the imaging apparatus (10); and

responsive to the detecting, biasing the movable subject support couch (30) into the docked position using the mated latch (82) as a first force anchor.

18. The method as set forth in claim 17, further including:

locking a couch brake (42) after the movable couch (30) is biased into the docked position; and

responsive to an unlocking of the couch brake (42), removing the biasing of the movable couch (30) into the docked position and unmating the latch (82) from the connecting region (50) of the imaging apparatus (10).

19. The method as set forth in claim 17, wherein the biasing of the movable subject support couch (30) into the docked position includes:

relatively drawing a second force anchor disposed on the movable couch (30) toward the first force anchor defined by the mated latch (82).

1/9






FIG 1





4/9





FIG 4







FIG 6

7/9



8/9





FIG 8



INTERNATIONAL SEARCH REPORT

PCT/IB 03/05305

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B5/055 A61B6/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHEDMinimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 567 894 A (BERGMAN CHARLES T) 4 February 1986 (1986-02-04) column 4, line 15 -column 5, line 35 ---	1-19
A	US 4 671 728 A (SCHMER JR FRANK M ET AL) 9 June 1987 (1987-06-09) column 4, line 21 -column 5, line 25 -----	1-19



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the International filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 February 2004

Date of mailing of the international search report

02/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Manschot, J

INTERNATIONAL SEARCH REPORT

PCT/IB 03/05305

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4567894	A	04-02-1986	NONE		
US 4671728	A	09-06-1987	EP	0209326 A2	21-01-1987
			JP	62014842 A	23-01-1987